SKSRT480GS
48-INCH GAS PRO RANGETOP WITH 6 BURNERS AND GRIDDLE

SKS | SIGNATURE KITCHEN SUITE

CHROMIUM GRIDDLE
The chromium griddle delivers consistent, even heating across the entire surface for professional results and the durable, polished finish resists scratches.

POWER-UP OR SIMMER DOWN
Three Ultra-High Burners deliver 23K BTUs of pure cooking power for better searing and quick stir frying Three Ultra-Low Burners simmer down to maintain temperatures as low as 100° to prepare delicate sauces and sugary confections.

BUILT-IN WOK GRATE
The two front burner grates are convertible for round-bottom wok cooking. Stir fry at home with professional-style results.

SMART KNOBS™
Each burner has a dedicated Smart Knob® featuring a large, illuminated display that makes it easy to read from across the room. Smart Knobs™ include a Wi-Fi function that let you see if the burner is on or off using the ThinQ® app.

Innovation

Wi-Fi Enabled for ThinQ® Control with iPhone / Android App	Yes
Remote Monitoring	Yes

Cooktop Features

Number of Burners	6 + Griddle
Continuous Grates	3
Wok Convertible Grate (On Front Burners)	Yes
Chromium Griddle Plate	1
Heating Element "ON" Indicator Light	Yes
LED Power Level Display	Yes

Cooktop Performance

Simmer – Max. BTU/h (NG)	
Left Rear	310 – 15,000
Center Rear	310 – 15,000
Right Rear	310 – 15,000
Left Front	650 – 23,000
Center Front	650 – 23,000
Right Front	650 – 23,000
Griddle BTU/h (NG)	18,000

SKSRT480GS
48-INCH GAS PRO RANGETOP WITH 6 BURNERS AND GRIDDLE

SKS | SIGNATURE KITCHEN SUITE

Controls

Knob Cooktop Controls w/LED Display	Yes

Cooktop / General Features

Sealed Gas Burners (Brass)	Yes
Surface Material	Black Porcelain
Stainless Steel Side Panels	Yes

Technical Specs

Energy Source	Natural Gas
Alternative Energy Source	LP Gas
LP Conversion Kit Included	Yes
Amp Rating at 120V	3.7 Amp
Required Power Supply	120VAC, 60 Hz, 15 Amp

Dimensions and Weight

Overall Width (inches)	47 7/8"
Overall Height Including Grates (inches)	8 15/16"
Overall Depth Including Knobs (inches)	28 15/16"
Overall Depth without Knobs (inches)	26 3/4"
Net Weight (approx.)	207 lbs.
Shipping Weight (approx.)	284 lbs.

Accessories

Included Accessories:

3 Wok Grates, Griddle Grease Tray

Warranty Summary*

|	
Limited Warranty, Parts & Labor	3 Years

Natural Gas or LP

Gas Rangetops are shipped by the factory to operate on natural gas. If the location / job site requires conversion from natural gas to propane (LP), utilize the included LP kit. Conversion must be done by a qualified installer or service technician.

SKSRT480GS
48-INCH GAS PRO RANGETOP WITH 6 BURNERS AND GRIDDLE

SKS | SIGNATURE KITCHEN SUITE

CUTOUT DIMENSIONS

48" (1219 mm) min. distance between overhead cabinets or combustible material†

13" (330 mm) max. cabinet depth

36" (914 mm) min. from bottom of hood to cooking surface

10" (254 mm) min. to combustible sidewall material (both sides)†

18" (457 mm) min.

Cooking Surface

48" (1219 mm) opening width

7 13/16" (198 mm)

4" (102 mm)

16" (406 mm)

24" (610 mm) min.
25" (635 mm) max.

36" (914 mm)

Electric & Gas supply located through bottom left rear corner of platform

Platform/Base 1" (25 mm) min. thickness

†As defined in the "National Fuel Gas Code" (ANSI Z223.1, Current Edition). Clearances from non-combustiblematerials are not part of the ANSI Z21.1 scope and are not certified by CSA. Clearances of less than 12" (305 mm) must be approved by the local codes and/or by the local authority having jurisdiction.

NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces, combustible materials cannot be located within this area. For island installation, 12" (305 mm) minimum clearance from back of rangetop.

Important Installation Information: Rangetops use a single phase, four-wire cable, 120/240 volt, 60 hertz, AC-only electrical supply with ground.

OVERALL PRODUCT DIMENSIONS

47 7/8" (1216 mm) width

countertop to cooking surface

1 5/32" (30 mm)

7 13/16" (198 mm)

27 15/16" (710 mm) to front edge

3 7/16" (87 mm) control panel depth

24 1/2" (622 mm)

26 3/4" (679 mm)

28 15/16" (735 mm) to front of knob